## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2000-357763

(43) Date of publication of application: 26.12.2000

(51)lnt.CI.

H01L 23/12 H01P 3/02 H01P 5/08

(21) Application number: 2000-024290

(71)Applicant: NEC CORP

(22)Date of filing:

01.02.2000

(72)Inventor: MARUHASHI KENICHI

ITO MASAHARU OHATA KEIICHI

(30)Priority

Priority number: 11105835

Priority date: 13.04.1999


Priority country : **JP** 

## (54) HIGH-FREQUENCY CIRCUIT BOARD

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a high-frequency circuit board which relaxes the size of a minimum line width/an interval required by a coplanar line at a small distance to a ground, which is low-cost and whose yield is high in the high-frequency circuit board on which the coplanar line is formed.

SOLUTION: In this high-frequency circuit board 1, a first dielectric layer 5, a conductor layer 6 and a second dielectric layer 7 are laminated in this order and are formed. A coplanar line 2 is formed on the conductor layer 6. A region, in which a semiconductor element 8 is mounted out of the second dielectric layer 7, is partially removed, and an opening part 3 is formed. In the opening part 3, the coplanar line 2 is partially exposed, and bumps 4 are formed. The semiconductor element 8 is connected via the bumps 4 to the coplanar line, which is formed on the conductor layer 6. A thickness H of the second dielectric layer is smaller than a thickness T of the semiconductor element 8.



## LEGAL STATUS

[Date of request for examination]

01.02.2000

[Date of sending the examiner's decision of

08.10.2002

rejection

[Kind of final disposal of application other than the examiner's decision of rejection or application

converted registration]

[Date of final disposal for application]

BEST AVAILABLE COPY

[Patent number] 3409767 [Date of registration] 20.03.2003 [Number of appeal against examiner's decision of 2002-21592

[Date of requesting appeal against examiner's decision of rejection] 07.11.2002

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

## BEST AVAILABLE COPY